SEP 2 4 2003 W

ROSĖNBERČ et al., Ser. No. 09/787,079

COPY OF ALL CLAIMS



- 1. (currently amended) A process for producing tablets by melt extrusion, in which an extrudable <u>pharmaceutical</u> mixture is heated and extruded in the form of a continuous product strip, the still deformable product strip is compressed to a continuous tablet belt, the individual tablets in the belt being connected together by product webs, the tablet belt is allowed to cool <u>to form a solidified tablet belt</u>, and the tablets are finally singulated and deflashed, wherein firstly the tablets are mechanically singulated in a continuous process, and then the singulated tablets are transported further and subsequently deflashed.
- (original) A process as claimed in claim 1, wherein a force with a component perpendicular to the plane of the tablet belt is allowed to act on the tablet belt for singulation of the tablet.
- (previously presented) A process as claimed in claim 2, wherein a force with a component perpendicular to the plane of the table belt is allowed to act on the tablet belt for singulation of the tablets.
- (previously presented) A process as claimed in claim 2, wherein the
 perpendicular force component is generated by diverting the solidified tablet belt
 out of its transport plane.
- (previously presented) A process as claimed in claim 3, wherein the parallel force component is generated by exerting a traction force on the solidified tablet belt.

ROSENBERG et al., Ser. No. 09/787,079

- 6. (canceled)
- 7. (currently amended) An apparatus as claimed in claim <u>12</u> 6, wherein the singulating means comprises at least one rotatable roller for diverting the tablet belt out of a transport plane of the first transport means.
- 8. (previously presented) An apparatus as claimed in claim 7, wherein the singulating means comprises two counter-rotating rollers which can be pressed against one another.
- 9. (currently amended) An apparatus as claimed in claim <u>12</u> 6, wherein the singulating means comprises at least one brush roller or embossed roller.
- 10. Cancel.
- 11. (currently amended) An apparatus as claimed in claim <u>12</u> 6, wherein a second transport means is provided between the singulating means and the deflashing means and comprises a shaking or vibrating unit.
- 12. (currently amended) An apparatus for producing tablets, comprising at least one extruder means for heating a pharmaceutical mixture, means for shaping a tablet belt from said extruded heated pharmaceutical mixture arranged downstream of said extruder,

first transport means for said tablet belt <u>comprises means for cooling the</u>

<u>extruded tablet belts and which is</u> arranged downstream of said shaping means, and

means for singulating and deflashing said tablets, wherein said means for singulating and deflashing said tablets comprise at least one singulating means arranged downstream of said first transport means, and at least one deflashing means

arranged downstream of said singulating meaans and spatially separate therefrom.